

DRYTEC AMERICA

Technical Data Sheet
SDM-5-06112024

TECHNICAL SPECS DATA SHEET

Drytec America Model Name	SDM-5
---------------------------	-------

GENERAL DATA

Purge Source	Dry Air
Purge Rate Adjustment	Fixed by an Orifice
Type Of Desiccant	Activated Alumina
Size Of Desiccant	3mm (1/8")
Body Material	Aluminium
Paint External	Electrostatic Powder Paint
Control Type	Crouzet
Purge Valve	Piston Valve
Remote Access	Available

REFERENCE DATA

**Designed Dew Point (°C / °F)	-40° / -40°
Max Ambient Temp (°C / °F)	50° / 122°
Min Ambient Temp (°C / °F)	1.6° / 34°
Max Inlet Temp (°C / °F)	50° / 122°
Max Rated Air Flow at 35°C (95°F) Inlet, 7 barg (100 psig) And 25°C (77°F) Ambient. (Nm ³ /h)	10 (inlet to the dryer)
Min Working Pressure (barg / psig)	4.5 / 65
Max Working Pressure (barg / psig)	16 / 232
Relief Valve Setting (barg / psig)	16 / 232

PERFORMANCE DATA

Pressure Drop (mbar / psi)	≤130 / 1.9
Avg Purge Rate (at -40 °C tdp)	15%
Cycle Time (For Two Towers)	300 Seconds
Regeneration Time (Per Tower)	120 Seconds
Cooling Time	N/A
Repressurization Time	30 Seconds
Dew Point Demand Control	Optional

ELECTRICAL DATA

Standard Voltage	110-230V / 1 Ph / 50-60 Hz
Full Load (Amps)	1.6 Amper
Min. Circuit Ampacity	1.6 Amper
Input Power (kW)	<0.1
Unit Average (kW)	<0.1

DIMENSIONAL DATA

Length (inch)	13.25
Width (inch)	12.6
Height (inch)	25
Weight (lbs)	37.5
Inlet-Outlet Connection	1/2"
Filters Included	X, Y, and P

DRYTEC AMERICA

Taking Air Treatment to New Heights

4121 Ohio Street
Michigan City, IN 46360
219-878-1550